

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 1/13
(30567989/SDS_CPA_US/EN)

1. Identification

Product identifier used on the label

PT B TRI-DIE PRESSURIZED

Recommended use of the chemical and restriction on use

Recommended use*: insecticide

* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Registrant:
Whitmire Micro-Gen Research Laboratories, Inc.
3568 Tree Court Industrial Blvd.
St. Louis, MO 63122

Other means of identification

Substance number: 546173
EPA Register number: 499-385
Synonyms: Pyrethrins + piperonyl butoxide + amorphous silica dioxide

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Asp. Tox.	1	Aspiration hazard
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 2/13
(30567989/SDS_CPA_US/EN)

Carc. STOT SE	1B 3 (Vapours may cause drowsiness and dizziness.)	Carcinogenicity Specific target organ toxicity — single exposure
Aquatic Acute Aquatic Chronic	2 2	Hazardous to the aquatic environment - acute Hazardous to the aquatic environment - chronic

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H319	Causes serious eye irritation.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P201	Obtain special instructions before use.
P273	Avoid release to the environment.
P271	Use only outdoors or in a well-ventilated area.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/gas/mist/vapours.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P391	Collect spillage.
P331	Do NOT induce vomiting.
P337 + P311	If eye irritation persists: Call a POISON CENTER or doctor/physician.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 3/13
(30567989/SDS_CPA_US/EN)

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Emergency overview

CAUTION:

KEEP OUT OF REACH OF CHILDREN.

Can cause moderate eye irritation.

Avoid contact with the skin, eyes and clothing.

Wash thoroughly after handling.

Avoid inhalation of mists/vapours.

Flammable Liquid

Aerosol container contains flammable gas under pressure.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
8003-34-7	0.6 %	pyrethrum
51-03-6	4.8 %	Piperonylbutoxide
112926-00-8	8.0 %	Silica gel, precipitated, crystalline free
67-64-1		Acetone
540-84-1		2,2,4-trimethylpentane
124-38-9		carbon dioxide
64742-47-8		Distillates (petroleum), hydrotreated light

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
8003-34-7	0.6 %	pyrethrum
51-03-6	4.8 %	Piperonylbutoxide
112926-00-8	8.0 %	Silica gel, precipitated, crystalline free
	86.6 %	Proprietary ingredients
67-64-1		Acetone
540-84-1		2,2,4-trimethylpentane
124-38-9		carbon dioxide
64742-47-8		Distillates (petroleum), hydrotreated light

4. First-Aid Measures

Description of first aid measures

General advice:

First aid providers should wear personal protective equipment to prevent exposure. Remove contaminated clothing. Move person to fresh air. If person is not breathing, call 911 or ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or physician for treatment advice. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

If inhaled:

Remove the affected individual into fresh air and keep the person calm.

If on skin:

Rinse skin immediately with plenty of water for 15 - 20 minutes.

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 4/13
(30567989/SDS_CPA_US/EN)

If in eyes:

Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.

If swallowed:

Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Have person sip a glass of water if able to swallow.

Most important symptoms and effects, both acute and delayed

Hazards: Vomiting may cause aspiration pneumonia due to the ingredients.

Indication of any immediate medical attention and special treatment needed

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
foam, dry powder, carbon dioxide

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon monoxide, carbon dioxide, hydrogen fluoride, halogenated hydrocarbons, halogenated compounds

The substances/groups of substances mentioned can be released in case of fire. Aerosol container contains flammable gas under pressure. Risk of explosion at excessive temperatures.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Evacuate area of all unnecessary personnel. Contain contaminated water/firefighting water. Do not allow to enter drains or waterways.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Take appropriate protective measures. Clear area. Shut off source of leak only under safe conditions. Extinguish sources of ignition nearby and downwind. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Environmental precautions

Do not discharge into the subsoil/soil. Do not discharge into drains/surface waters/groundwater. Contain contaminated water/firefighting water. A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities. This product is regulated by CERCLA ('Superfund').

Methods and material for containment and cleaning up

Dike spillage. Pick up with suitable absorbent material. Spilled substance/product should be recovered and applied according to label rates whenever possible. If application of spilled substance/product is not possible, then spills should be contained, solidified, and placed in suitable

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 5/13
(30567989/SDS_CPA_US/EN)

containers for disposal. After decontamination, spill area can be washed with water. Collect wash water for approved disposal.

7. Handling and Storage

Precautions for safe handling

RECOMMENDATIONS ARE FOR MANUFACTURING, COMMERCIAL BLENDING, AND PACKAGING WORKERS. PESTICIDE APPLICATORS & WORKERS must refer to the Product Label and Directions for Use attached to the product. Provide good ventilation of working area (local exhaust ventilation if necessary). Keep away from sources of ignition - No smoking. Keep container tightly sealed. Protect against heat. Handle and open container with care. Do not open until ready to use. Once container is opened, content should be used as soon as possible. Provide means for controlling leaks and spills. Follow label warnings even after container is emptied. The substance/product may be handled only by appropriately trained personnel. Avoid all direct contact with the substance/product. Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts/mists/vapours. Wear suitable personal protective clothing and equipment.

Protection against fire and explosion:

Aerosol container contains flammable gas under pressure. The relevant fire protection measures should be noted. Fire extinguishers should be kept handy. Avoid all sources of ignition: heat, sparks, open flame. Avoid extreme heat. Ground all transfer equipment properly to prevent electrostatic discharge. Electrostatic discharge may cause ignition.

Conditions for safe storage, including any incompatibilities

Segregate from incompatible substances. Segregate from foods and animal feeds. Segregate from textiles and similar materials.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE)

Further information on storage conditions: Protect containers from physical damage. Store in a cool, dry, well-ventilated area. Avoid all sources of ignition: heat, sparks, open flame.

Storage stability:

May be kept indefinitely if stored properly.

If an expiry date is mentioned on the packaging/label this takes priority over the statements on storage duration in this safety data sheet.

Protect from temperatures above: 130 °F

Explosive at or above indicated temperature.

8. Exposure Controls/Personal Protection

Users of a pesticidal product should refer to the product label for personal protective equipment requirements.

Components with occupational exposure limits

Acetone	OSHA PEL ACGIH TLV	PEL 1,000 ppm 2,400 mg/m ³ ; TWA value 500 ppm ; STEL value 750 ppm ;
carbon dioxide	OSHA PEL ACGIH TLV	PEL 5,000 ppm 9,000 mg/m ³ ; TWA value 5,000 ppm ; STEL value 30,000 ppm ;
2,2,4-trimethylpentane	OSHA PEL ACGIH TLV	PEL 500 ppm 2,350 mg/m ³ ; TWA value 300 ppm ; TWA value 300 ppm ;

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 6/13
(30567989/SDS_CPA_US/EN)

Distillates (petroleum),
hydrotreated light

ACGIH TLV

TWA value 200 mg/m³ Non-aerosol (total hydrocarbon vapor);
Application restricted to conditions in which there are negligible aerosol exposures.
Skin Designation Non-aerosol (total hydrocarbon vapor);
The substance can be absorbed through the skin.

Advice on system design:

Whenever possible, engineering controls should be used to minimize the need for personal protective equipment.

Personal protective equipment

RECOMMENDATIONS FOR MANUFACTURING, COMMERCIAL BLENDING, AND PACKAGING WORKERS:

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator. For situations where the airborne concentrations may exceed the level for which an air purifying respirator is effective, or where the levels are unknown or Immediately Dangerous to Life or Health (IDLH), use NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection:

Chemical resistant protective gloves, Protective glove selection must be based on the user's assessment of the workplace hazards.

Eye protection:

Safety glasses with side-shields. Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:

RECOMMENDATIONS FOR MANUFACTURING, COMMERCIAL BLENDING, AND PACKAGING WORKERS Wear long sleeved work shirt and long work pants in addition to other stated personal protective equipment. Work place should be equipped with a shower and an eye wash. Handle in accordance with good industrial hygiene and safety practice. Personal protective equipment should be decontaminated prior to reuse. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). Take off immediately all contaminated clothing. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift. No eating, drinking, smoking or tobacco use at the place of work. Keep away from food, drink and animal feeding stuffs.

9. Physical and Chemical Properties

Form: liquid, suspension
Odour: characteristic, of acetone

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 7/13
(30567989/SDS_CPA_US/EN)

Odour threshold:		Not determined due to potential health hazard by inhalation.
Colour:	off-white	
pH value:	approx. 5.8	(23.4 °C)
Aerosol foam	> 18 in	
flammability test:	no flashback	
NFPA 30B flammability:	Level 2 Aerosol	
Lower explosion limit:		As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Upper explosion limit:		As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Density:	0.8442 g/cm3	(20 °C)
Vapour density:		not applicable
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Self-ignition temperature:		Based on its structural properties the product is not classified as self-igniting.
Thermal decomposition:	carbon monoxide, carbon dioxide, halogenated hydrocarbons, hydrogen fluoride	Stable at ambient temperature. If product is heated above decomposition temperature toxic vapours may be released. To avoid thermal decomposition, do not overheat.
Viscosity, dynamic:	approx. 110 cps	(21.3 °C)
Solubility in water:		slightly soluble

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is chemically stable.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid prolonged storage. Avoid electro-static discharge. Avoid contamination. Avoid prolonged exposure to extreme heat. Avoid extreme temperatures.

Incompatible materials

No substances known that should be avoided.

Hazardous decomposition products

Decomposition products:

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 8/13
(30567989/SDS_CPA_US/EN)

No hazardous decomposition products if stored and handled as prescribed/indicated., Prolonged thermal loading can result in products of degradation being given off.

Thermal decomposition:

Possible thermal decomposition products:

carbon monoxide, carbon dioxide, halogenated hydrocarbons, hydrogen fluoride

Stable at ambient temperature. If product is heated above decomposition temperature toxic vapours may be released. To avoid thermal decomposition, do not overheat.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Relatively nontoxic after single ingestion. Relatively nontoxic after short-term skin contact. Relatively nontoxic after short-term inhalation.

Oral

Type of value: LD50

Species: rat (female)

Value: > 5,000 mg/kg

Inhalation

Type of value: LC50

Species: rat (male/female)

Value: > 2.11 mg/l

Exposure time: 4 h

Dermal

Type of value: LD50

Species: rat (male/female)

Value: > 5,000 mg/kg

Irritation / corrosion

Assessment of irritating effects: May cause slight irritation to the skin. May cause moderate but temporary irritation to the eyes.

Skin

Species: rabbit

Result: Slightly irritating.

Eye

Species: rabbit

Result: Slightly irritating.

Sensitization

Assessment of sensitization: Skin sensitizing effects were not observed in animal studies.

Buehler test

Species: guinea pig

Result: Skin sensitizing effects were not observed in animal studies.

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 9/13
(30567989/SDS_CPA_US/EN)

Chronic Toxicity/Effects

Genetic toxicity

Information on: pyrethrum

Assessment of mutagenicity: Mutagenicity tests revealed no genotoxic potential. The product has not been tested. The statement has been derived from the properties of the individual components.

No mutagenic effects reported.

Carcinogenicity

Information on: pyrethrum

Assessment of carcinogenicity: The results of various animal studies gave no indication of a carcinogenic effect. The product has not been tested. The statement has been derived from the properties of the individual components.

Not Likely to Be Carcinogenic to Humans.

Reproductive toxicity

Information on: pyrethrum

Assessment of reproduction toxicity: No reproductive toxic effects reported.

Information on: Acetone

Assessment of reproduction toxicity: As shown in animal studies, the product may cause damage to the testes after repeated high exposures that cause other toxic effects.

Teratogenicity

Information on: pyrethrum

Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Symptoms of Exposure

12. Ecological Information

Toxicity

Toxicity to fish

Information on: pyrethrum

LC50 (96 h) 0.0052 mg/l, Oncorhynchus mykiss (static)

LC50 (96 h) 0.01 mg/l, Lepomis macrochirus

Information on: piperonyl butoxide

LC50 (96 h) 5.37 mg/l, Lepomis macrochirus

Information on: Acetone

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 10/13
(30567989/SDS_CPA_US/EN)

LC50 (96 h) 6,210 mg/l, *Pimephales promelas* (OECD 203; ISO 7346; 84/449/EEC, C.1, Flow through.)

The statement of the toxic effect relates to the analytically determined concentration.

LC50 (96 h) 5,540 mg/l, *Oncorhynchus mykiss* (Fish test acute, static)

Nominal concentration.

Information on: Silicon dioxide

LC50 (96 h) > 10,000 mg/l, *Brachydanio rerio* (OECD 203; ISO 7346; 84/449/EEC, C.1, static) other TS

Aquatic invertebrates

Information on: pyrethrum

EC50 (48 h) 0.012 mg/l, *Daphnia magna*

No observed effect concentration (28 d) 0.00086 mg/l, *Daphnia magna*

EC50 (48 h) 0.0014 mg/l, *Mysidopsis bahia*

Information on: piperonyl butoxide

LC50 (48 h) 0.51 mg/l, *Daphnia magna*

Information on: Acetone

LC50 (48 h) 8,800 mg/l, *Daphnia pulex* (*Daphnia* test acute, static)

Nominal concentration.

LC50 (24 h) 2,100 mg/l, *Artemia salina* (*Daphnia* test acute, static)

Nominal concentration.

Information on: Silicon dioxide

EC50 (24 h) > 1,000 mg/l, *Daphnia magna* (OECD Guideline 202, part 1)

other TS

Aquatic plants

Information on: pyrethrum

No data available.

Information on: piperonyl butoxide

EC50 14.9 mg/l, *Chlorella fusca*

Information on: Acetone

Toxic limit concentration (8 d) 530 mg/l (biomass), *Microcystis aeruginosa* (DIN 38412 Part 9, static)

Nominal concentration.

Information on: Silicon dioxide

No observed effect concentration (72 h) 10,000 mg/l (biomass), *Scenedesmus subspicatus* (OECD Guideline 201, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Nominal concentration.

other TS

Bioaccumulative potential

Assessment bioaccumulation potential

The product has not been tested. The statement has been derived from the properties of the individual components.

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 11/13
(30567989/SDS_CPA_US/EN)

13. Disposal considerations

Waste disposal of substance:

Pesticide wastes are regulated. Improper disposal of excess pesticide, spray mix or rinsate is a violation of federal law. If pesticide wastes cannot be disposed of according to label instructions, contact the State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container disposal:

Do not cut, puncture, crush, or incinerate empty aerosol containers. Consult state or local disposal authorities for approved alternative procedures such as container recycling. Empty aerosol cans may meet the definition of RCRA D003. Consult local and/or regional EPA for further guidance.

14. Transport Information

Land transport

USDOT

Hazard class: 2.1
ID number: UN 1950
Hazard label: 2.1
Proper shipping name: AEROSOLS (contains 1,1-DIFLUOROETHANE, ACETONE/DIMETHYLKETONE)

Sea transport

IMDG

Hazard class: 2.1
ID number: UN 1950
Hazard label: 2.1
Marine pollutant: NO
Proper shipping name: AEROSOLS (contains 1,1-DIFLUOROETHANE, ACETONE/DIMETHYLKETONE)

Air transport

IATA/ICAO

Hazard class: 2.1
ID number: UN 1950
Hazard label: 2.1
Proper shipping name: AEROSOLS, FLAMMABLE (contains 1,1-DIFLUOROETHANE, ACETONE/DIMETHYLKETONE)

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US blocked / not listed

Crop Protection TSCA, US released / exempt

EPCRA 311/312 (Hazard categories): Acute; Chronic

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10
Version: 3.0

Page: 12/13
(30567989/SDS_CPA_US/EN)

EPCRA 313:

<u>CAS Number</u>	<u>Chemical name</u>
51-03-6	Piperonylbutoxide

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
5000 LBS	67-64-1	Acetone
1000 LBS	540-84-1	2,2,4-trimethylpentane
1 LBS	8003-34-7	Pyrethrins

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
NJ	51-03-6	Piperonylbutoxide
MA, NJ, PA	112926-00-8	Silica gel, precipitated, crystalline free
MA, NJ, PA	67-64-1	Acetone
MA, NJ, PA	540-84-1	2,2,4-trimethylpentane
MA, NJ, PA	124-38-9	carbon dioxide
MA, NJ, PA	64742-47-8	Distillates (petroleum), hydrotreated light

Labeling requirements under FIFRA

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label.

CAUTION:

KEEP OUT OF REACH OF CHILDREN.

May cause moderate but temporary irritation to the eyes.

Avoid contact with the skin, eyes and clothing.

Wash thoroughly after handling.

Avoid inhalation of mists/vapours.

Flammable Liquid

Aerosol container contains flammable gas under pressure.

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2014/09/10

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS

Safety Data Sheet

PT B TRI-DIE PRESSURIZED

Revision date : 2014/09/10

Page: 13/13

Version: 3.0

(30567989/SDS_CPA_US/EN)

PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET